

	Nynas UK AB North Road, Ellesmere Port CH65 1AJ, United Kingdom		Version: 2012-3																																											
			18	1162																																										
			CPR-GB-0007																																											
			www.nynas.com																																											
EN 12591:2009		Paving Grade Bitumen		100/150																																										
Nynas 100/150																																														
Construction and maintenance of roads, airfields and other paved areas																																														
<table border="1"> <thead> <tr> <th>Property</th> <th>Method</th> <th>Unit</th> <th>Values</th> </tr> </thead> <tbody> <tr> <td>Penetration at 25 °C</td> <td>EN 1426</td> <td>mm/10</td> <td>100-150</td> </tr> <tr> <td>Softening Point Ring & Ball</td> <td>EN 1427</td> <td>°C</td> <td>39-47</td> </tr> <tr> <td colspan="5">RESISTANCE TO HARDENING AT 163 °C</td> </tr> <tr> <td>Retained penetration at 25 °C</td> <td>EN 1426</td> <td>%</td> <td>≥ 43</td> </tr> <tr> <td>Increase in softening point</td> <td>EN 1427</td> <td>°C</td> <td>≤ 10</td> </tr> <tr> <td>Penetration index</td> <td>Annex A</td> <td></td> <td>-1.5 to + 0.7</td> </tr> <tr> <td>Dynamic viscosity at 60 °C</td> <td>EN 13302</td> <td>Pa • s</td> <td>NR</td> </tr> <tr> <td>Fraass Breaking point</td> <td>EN 12593</td> <td>°C</td> <td>≤ -12</td> </tr> <tr> <td colspan="3">Regulated Dangerous Substances</td> <td colspan="2">NPD</td> </tr> </tbody> </table>					Property	Method	Unit	Values	Penetration at 25 °C	EN 1426	mm/10	100-150	Softening Point Ring & Ball	EN 1427	°C	39-47	RESISTANCE TO HARDENING AT 163 °C					Retained penetration at 25 °C	EN 1426	%	≥ 43	Increase in softening point	EN 1427	°C	≤ 10	Penetration index	Annex A		-1.5 to + 0.7	Dynamic viscosity at 60 °C	EN 13302	Pa • s	NR	Fraass Breaking point	EN 12593	°C	≤ -12	Regulated Dangerous Substances			NPD	
Property	Method	Unit	Values																																											
Penetration at 25 °C	EN 1426	mm/10	100-150																																											
Softening Point Ring & Ball	EN 1427	°C	39-47																																											
RESISTANCE TO HARDENING AT 163 °C																																														
Retained penetration at 25 °C	EN 1426	%	≥ 43																																											
Increase in softening point	EN 1427	°C	≤ 10																																											
Penetration index	Annex A		-1.5 to + 0.7																																											
Dynamic viscosity at 60 °C	EN 13302	Pa • s	NR																																											
Fraass Breaking point	EN 12593	°C	≤ -12																																											
Regulated Dangerous Substances			NPD																																											