

	Nynas UK AB North Road, Ellesmere Port CH65 1AJ, United Kingdom		Version: 2012-3																																																	
			18	1162																																																
			CPR-GB-0056																																																	
			www.nynas.com																																																	
EN 13808:2013		Emulsion		C69B3																																																
Nynas Spraymuls																																																				
Surface dressing																																																				
<table border="1"> <thead> <tr> <th>Property</th> <th>Method</th> <th>Unit</th> <th>Values</th> </tr> </thead> <tbody> <tr> <td colspan="4"><b>EMULSION</b></td> </tr> <tr> <td>Breaking value</td> <td>EN 13075-1</td> <td></td> <td>70-155</td> </tr> <tr> <td>Efflux time 4 mm at 40 °C</td> <td>EN 12846-1</td> <td>s</td> <td>5-70</td> </tr> <tr> <td>Adhesivity with reference aggregate</td> <td>EN 13614</td> <td></td> <td>≥ 90</td> </tr> <tr> <td colspan="4"><b>RECOVERED BINDER</b></td> </tr> <tr> <td>Penetration at 25 °C</td> <td>EN 1426</td> <td>mm/10</td> <td>≤ 220</td> </tr> <tr> <td>Softening Point Ring &amp; Ball</td> <td>EN 1427</td> <td>°C</td> <td>≥ 39</td> </tr> <tr> <td colspan="4"><b>STABILISED BINDER</b></td> </tr> <tr> <td>Penetration at 25 °C</td> <td>EN 1426</td> <td>mm/10</td> <td>≤ 150</td> </tr> <tr> <td>Softening Point Ring &amp; Ball</td> <td>EN 1427</td> <td>°C</td> <td>≥ 43</td> </tr> <tr> <td colspan="3">Regulated Dangerous Substances</td> <td>NPD</td> </tr> </tbody> </table>					Property	Method	Unit	Values	<b>EMULSION</b>				Breaking value	EN 13075-1		70-155	Efflux time 4 mm at 40 °C	EN 12846-1	s	5-70	Adhesivity with reference aggregate	EN 13614		≥ 90	<b>RECOVERED BINDER</b>				Penetration at 25 °C	EN 1426	mm/10	≤ 220	Softening Point Ring & Ball	EN 1427	°C	≥ 39	<b>STABILISED BINDER</b>				Penetration at 25 °C	EN 1426	mm/10	≤ 150	Softening Point Ring & Ball	EN 1427	°C	≥ 43	Regulated Dangerous Substances			NPD
Property	Method	Unit	Values																																																	
<b>EMULSION</b>																																																				
Breaking value	EN 13075-1		70-155																																																	
Efflux time 4 mm at 40 °C	EN 12846-1	s	5-70																																																	
Adhesivity with reference aggregate	EN 13614		≥ 90																																																	
<b>RECOVERED BINDER</b>																																																				
Penetration at 25 °C	EN 1426	mm/10	≤ 220																																																	
Softening Point Ring & Ball	EN 1427	°C	≥ 39																																																	
<b>STABILISED BINDER</b>																																																				
Penetration at 25 °C	EN 1426	mm/10	≤ 150																																																	
Softening Point Ring & Ball	EN 1427	°C	≥ 43																																																	
Regulated Dangerous Substances			NPD																																																	