



## DECLARATION OF PERFORMANCE

CPR-GB-0054

1. The product-type: Cationic Bitumen Emulsion C69B3
2. Product name: Nynas K1-70
3. Intended use or uses of the construction product: Surface dressing
4. Name and contact address of the manufacturer: North Road, Ellesmere Port CH65 1AJ, United Kingdom
5. System of assessment and verification of constancy of performance: System 2+
6. Det Norske Veritas, notified body identification no. 1162, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control (under system 2+) and issued the certificate of conformity of the factory production control.  
Harmonised Technical Specification EN 13808:2013
7. Declared performance

Method	Method	Unit	Values
EMULSION			
Breaking value	EN 13075-1		70-155
Efflux time 4 mm at 40 °C	EN 12846-1	s	5-70
Adhesivity with reference aggregate	EN 13614		≥ 90
RECOVERED BINDER			
Penetration at 25 °C	EN 1426	mm/10	≤ 220
Softening Point Ring & Ball	EN 1427	°C	≥ 39
STABILISED BINDER			
Penetration at 25 °C	EN 1426	mm/10	≤ 150
Softening Point Ring & Ball	EN 1427	°C	≥ 43
Regulated Dangerous Substances			NPD

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Eastham 2018-01-29 Signed for and on behalf of the manufacturer by:



Version:

2012-3

Jim Christie

Business Area Manager UK & WE