



DECLARATION OF PERFORMANCE

CPR-GB-0055

1. The product-type: Cationic Bitumen Emulsion C65BP5
2. Product name: Nynas Micromuls
3. Intended use or uses of the construction product: Sealing
4. Name and contact address of the manufacturer: North Road, Ellesmere Port CH65 1AJ, United Kingdom
5. System of assessment and verification of constancy of performance: System 2+
6. Det Norske Veritas, notified body identification no. 1162, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control (under system 2+) and issued the certificate of conformity of the factory production control.
Harmonised Technical Specification EN 13808:2013
7. Declared performance

Method	Method	Unit	Values
EMULSION			
Breaking value	EN 13075-1		> 170
Efflux time 2 mm at 40 °C	EN 12846-1	s	15-70
Adhesivity with reference aggregate	EN 13614		≥ 90
RECOVERED BINDER			
Penetration at 25 °C	EN 1426	mm/10	≤ 150
Softening Point Ring & Ball	EN 1427	°C	≥ 50
Cohesion - Force Ductility at 5 °C	EN 13589	J/cm ²	≥ 1
STABILISED BINDER			
Penetration at 25 °C	EN 1426	mm/10	≤ 100
Softening Point Ring & Ball	EN 1427	°C	≥ 55
Cohesion - Force Ductility at 5 °C	EN 13589	J/cm ²	≥ 2
Regulated Dangerous Substances			NPD

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Eastham 2018-01-29 Signed for and on behalf of the manufacturer by:



A handwritten signature in black ink, appearing to read "Jim Christie". The signature is written in a cursive style with a large, prominent initial 'J'.

Jim Christie
Business Area Manager UK & WE

Version: 2012-5