

## Spraymuls

Spraymuls emulsion is a high bitumen cationic road emulsion designed to be hot applied as a surface dressing binder

### Product Data Sheet (PDS)

**Table 1: Specification information**

Test description	Method	Unit	Min	Max	
<b>Binder content</b>	EN 1428	%	67	71	
<b>Efflux time STV, 4 mm, 40°C</b>	EN 12846	s	5	70	
<b>Residue on seive, 0.5mm</b>	EN 1429	% w/w	-	0.5	
<b>Adhesivity</b>	EN 13614	% coating	90	-	
<b>Breaking Behaviour</b>	EN13075-1	-	70	155	
<b>Recovered binder</b>	<b>Consistency at intermediate service</b>	EN 1426	0.1mm	-	220
	<b>Consistency at elevated service</b>	EN 1427	°C	39	-
<b>Stabilised binder</b>	<b>Consistency at intermediate service</b>	EN 1426	0.1mm	-	150
	<b>Consistency at elevated service</b>	EN 1427	°C	43	-

\* For specific information on handling and storage please refer to the Product Information and Safety Data sheets.

**This product fulfils EN 13808 requirements for Bituminous emulsion Spraymuls and is CE marked**

Nynas UK  
North Road, Ellesmere Port  
CH65 1AJ South Wirral  
United Kingdom (UK)  
T +44 151 327 31 71  
F +44 151 327 61 95  
E bitumen.uk@nynas.com  
W www.nynas.com

Nynas UK  
East Camperdown Street  
DD1 3LG Dundee  
United Kingdom (UK)  
T +44 1382 46 22 11  
F +44 1382 45 03 08

Although the data reported in the present document is, to the best of our knowledge, accurate and reliable, Nynas shall not be liable for any loss or damage that may occur.

SDS available on [nynas.com](http://nynas.com)

Spraymuls